

## Dog Bone Pavers

The Rubber & Resin Specialists

**PROFILE:** LOW

**PATTERN:** DOG BONE SHAPE

**SIZE:** 200mm x 165mm

**THICKNESS:** 43mm

**COLOURS:** BLACK, RED & GREEN

other colours available upon request



A high density moulded rubber crumb paver with excellent grip for horses even in wet and cold weather. Ideal for Horse walkers, Racecourses, Stable Yards, Walkways and all other areas of movement and activity.

For heavy traffic areas we recommend bonding the pavers with Quattro's Superflex Membrane.

Can also be used for general areas of paving offering a warm, safe and comfortable surface.

Pavers can be supplied for self fitting.

Available in Black, Red or Green.



**Equestrian • Agricultural • Gym • Play**

Quattro Products Limited, Milestone House Ind Est, Penrith, Cumbria, CA11 9NQ

Tel: 01768864977 Email: [enq@quattro rubber and resin.co.uk](mailto:enq@quattro rubber and resin.co.uk) Web: [www.quattro rubber and resin.co.uk](http://www.quattro rubber and resin.co.uk)



### TECHNICAL DATA

Material Compound:	Recycled rubber bounded by Polyurethane
Approximate Dimensions:	200mm x 165mm x 43mm
Colours:	Black, Red & Green
Tolerance:	+/- 2mm
Density:	900kg/m <sup>3</sup>
Tensile Strength:	1.20 N/mm <sup>2</sup> following DIN EN ISO 1798
Slip Resistance:	Mean correct Pendulum Test Value 48 to 50 using a standard skid resistance pendulum test B.S. EN 13036-4:2011 (RECOMMENDED MINIMUM VALUE OF 40)
Long term thermal stability:	- 40°C ... +80°C
Short term thermal stability:	Up to +110°C
Colour stability:	Colour may fade out with UV exposure over time
Chemical resistance:	Resistance to weak acids and lyes conditionally resistant
Weight per m <sup>2</sup> :	43mm @ 38.7kg
Pieces per m <sup>2</sup> :	35



**Equestrian • Agricultural • Gym • Play**

Quattro Products Limited, Milestone House Ind Est, Penrith, Cumbria, CA11 9NQ

Tel: 01768864977 Email: [enq@quattrorubberandresin.co.uk](mailto:enq@quattrorubberandresin.co.uk) Web: [www.quattrorubberandresin.co.uk](http://www.quattrorubberandresin.co.uk)

