QUATTRO®

THE RUBBER & RESIN SPECIALIST

Trough Resurfacer

Concrete & Trough Resurfacer

A rapid setting pre made kit to repair feed passage ways and feed troughs plus much more.

Easy to use, simple to mix resin components with dry products and trowel over damaged area.

Coverage rate of 2.5m2 at 5mm thick with a maximum application thickness of 10mm in one application.

Main product properties

- Effluent resistant
- Easy to mix & apply
- Very hard wearing
- Resin bonded for extra strength
- Will feather edge
- Stands tractors, livestock traffic
- Non hazardous
- Long life expectancy

24kg

20kg Aggregate

4L Resin Additive

20.5L bucket

Application

In the mixing bucket provided is the aggregate and resin additive.

Step 1 - Prepare the surface to be treated - clean off and remove any standing water.

Step 2 - Remove the resin additive and pre mix the aggregate if separated.
Add the resin additive to the aggregate and mix well.

Step 3 - Once mixed pour resurfacer on to the surface.

Step 4 - Spread over the area with a trowel.

Leave to cure for around 24 hours or until completely hardened.

PLEASE NOT A MAXIMUM THICKNESS OF 10MM PER APPLICATION

Quattro Products Limited, Milestone House Industrial Estate, Penrith, Cumbria CA11 9NQ

www.quattrorubberandresin.co.uk Tel: 01768864977 enq@quattrorubberandresin.co.uk